



TEXTURE ENHANCER

Cementitious Antiquing Agent

PRODUCT DESCRIPTION

Deco-Crete Texture Enhancer is a proprietary blend of pigments, cement, and specialized carriers. When mixed with water and applied to stamped concrete, overlays, and other textured surfaces, it creates a permanent secondary color. Proper application allows the material to settle into low areas, enhancing depth, contrast, and overall surface definition.

TECHNICAL INFORMATION

+ Coverage.....1500 - 2500 Sq. Ft. Per Container

RECOMMENDED APPLICATIONS

- + Stamped Concrete
- + Concrete Overlays
- + Textured Repairs & Resurfaces
- + Decorative Walkways & Patios
- + Interior or Exterior Use



QUICK FACTS

- + Sprayable or Brush Applied
- + Precise Control Over Accent Color Intensity on Stamped Concrete
- + Adds Accent Color to Old or New Stamped Concrete/Textured Concrete & Overlays
- + 20 Colors Available - Designed to Match Deco-Crete Antique Release Agents



TEXTURE ENHANCER

Cementitious Antiquing Agent

APPLICATION INSTRUCTIONS

*Texture Enhancer must be applied to **unsealed** concrete. Do not apply to sealed concrete surfaces. All existing sealer must be removed before applying Texture Enhancer.*

MIXING

Add 1 scoop of Deco-Crete Texture Enhancer per 1 gallon of clean water. Mix vigorously with a paddle mixer and drill until the powder is incorporated into the water.

APPLICATION

Texture Enhancer can then be applied using a pump-up sprayer or soft applicator brush, spreading evenly over the entire surface of the slab. During application, the product must be kept agitated to avoid settling at the bottom of the container. It is important to maintain a wet edge to avoid brush marks. Slightly dampening the slab in warm weather is recommended to give Texture Enhancer adequate time to settle before drying out, helping to avoid brush marks.

SEALING

It's important to seal the concrete after Texture Enhancer has been applied to bring out the true colors and keep Texture Enhancer in place. D-One Sealer is the preferred sealer for most applications. Even if the Texture Enhancer appears dry after only a few hours, the concrete will still be too saturated for proper sealer application. **It is crucial to allow Texture Enhancer to fully dry 24 hours before applying sealer.**

WARRANTY

This product is not for public use and is intended for use by licensed contractors who are experienced and trained in its use. It is warranted to be of uniform quality with manufacturing tolerances. The manufacturer has no control over the use of this product; therefore, no warranty, expressed or implied, is or can be made either as to the effects or results of such use. In any case, the manufacturer's obligations shall be limited to refunding the purchase price or replacing the defective material. The end user shall be responsible for determining the product's suitability and assumes all risks and liability.



Check out our video about Texture Enhancer on our YouTube channel by scanning the QR code, or check out our other social media accounts listed here.

